

FLUID DELIVERY DEVICE**RELATED APPLICATION**

5 This application is related to and claims priority in,
coping U.S. Provisional Application Ser. No. 60/250,903,
filed December 2, 2000, the disclosures of which are
incorporated herein by reference.

BACKGROUND OF THE INVENTION

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

1. Field of the Invention

15 The present invention relates to an apparatus or device
that warms or heats lotion. More particularly, the present
invention relates to an apparatus that warms or heats and
dispenses, either manually or electrically, a warmed lotion,
such as, but not limited to, a hand or body lotion.

20

2. Description of the Prior Art

 There are devices that are commercially available that
dispense liquids, such as lotions. There are devices

commercially available that heat fluids. There are also devices commercially available that heat and dispense fluids from containers having a propellant. However, heretofore, there has been a need for a device that efficiently warms and dispenses a
5 lotion, such as a hand or body lotion, from a container.

DESCRIPTION OF THE FIGURES

10 Fig. 1 is a perspective view of a warmer and dispenser device of the present invention;

15 Fig. 2 is a cross-sectional view of a first embodiment of the device of Fig. 1 taken along line 2-2 of Fig. 1;

Fig. 3 is a plan view of the removable container of the device of Fig. 1;

20 Fig. 4 is a cross-sectional view of the container of Fig. 3 taken along line 4-4 of Fig. 3;

Fig. 5 is a plan view of the container top of the device of Fig. 1;

Fig. 6 is a cross-sectional view of a second embodiment of the device of Fig. 1 taken along line 2-2 of Fig. 1;

Fig. 7 is a perspective view of an alternative warming
5 system of the device of Fig. 1;

Fig. 8 is a perspective view of an alternative warming system of the device of Fig. 1;

10 Fig. 9 is a perspective view of an alternative warming system of the device of Fig. 1;

Fig. 10 is a perspective view of an alternative warming system of the device of Fig. 1; and
15

Fig. 11 is a flow chart depicting a method for warming and dispensing lotion according to the device of Fig. 1.

20 SUMMARY OF THE INVENTION

It is an object of the present invention to provide a fluid warmer and dispenser device.

It is another object of the present invention to provide such a device that warms and/or heats lotions, such as hand and body lotions.

5 It is yet another object of the present invention to provide such a device that dispenses the lotion by a pump.

It is a further object of the present invention to provide such a device that simplifies the lotion filling process.

10 It is yet a further object of the present invention to provide such a device with a more efficient heating process.

15 These and other objects and advantages of the present invention are achieved by the lotion warmer and dispenser or system of the present invention (hereinafter "warmer") that provides a lotion to the user at a desired temperature. The warmer includes a delivery system, a supply or reservoir, and a warming or warmer system. Preferably, the delivery system, supply, and warming system form an assembled unit.

20 In a preferred embodiment, the warmer of the present inventions heats only a small amount of the lotion in the aluminum tube in line between the output and the lotion supply.

Since the warmer does not have to provide heat to the entire reservoir of the lotion, a rapid heat up time is provided. Additionally, it is important that the lotion not be overheated as the formula of most lotions will degrade and/or separate when overheated. The temperature controller of the present invention also allows for almost no temperature overshoot, further reducing the likelihood of degrading the lotion. Moreover, the present invention isolates the electrical components, thus reducing the likelihood of injury if the warmer is accidentally exposed to wet conditions.

DESCRIPTION OF THE INVENTION

Referring to the figures and particularly to Figs. 1 and 2, there is provided a system or warmer generally designated by reference numeral 10 is shown. Warmer 10 has a delivery system 20, a supply or reservoir 40, and a warming or warmer system 50. Preferably, delivery system 20, supply 40, and warming system 50 form an assembled unit 12.

Warmer 10 dispenses lotion at a desired temperature. The desired temperature is preferably in a range from about 30° to

about 60°C. More preferably, the desired temperature is about 45°C. Warmer 10 also has a mechanism to allow the consumer to turn on or shut off power to the warmer. In a preferred embodiment, warmer 10 automatically shuts off after it has been

5 "on" for about 1 hour.

As shown in Fig. 2, delivery system 20 has a pump mechanism, such as, for example, a manual pump 22. The pump 22 delivers lotion from supply 40 to lotion warming system 50 and, then, to the user via an output section 60. In the preferred embodiment, output section 60 is a downwardly directed spout. A power cord (not shown) delivers power from a standard household electrical supply to warmer 10. Alternatively, warmer 10 has a battery (not shown) that delivers power to the warmer. The

10 pumping mechanism is either manual (as in the preferred embodiment) or electric.

15

Referring to Figs. 2 through 5, supply 40 has a container 42 for holding lotion. Preferably, container 42 is refillable.

20 More preferably, container 42 has a removable container top 44. By way of example, container 42 holds between about 2 to about 20 fluid ounces of lotion, and preferably between about 6 to about 16 fluid ounces of lotion. Top 44 removably seals

container 42. Container 42 and top 44 are preferably made of dishwasher safe material, such as plastic, aluminum, metal or any combination thereof.

5 Referring to Figs. 3 through 5, assembly 49 (by way of top 44) is adapted to be connected to container 42. Preferably, top 44 is adapted to be connected to container 42 by a connector 47. In a preferred embodiment, connector 47 of container 42 engages with tab 147 of container top 44. This allows a quick
10 connection that requires the user to only rotate container 42 not more than 180 degrees with respect to enclosed assembly 49. The removability of container 42 is a further advantage of the present invention since it allows for easy refilling of warmer
15 10.

Referring to Figs. 1 and 2, warmer 10 also has an upper lid 46 and a lower lid 48. Upper lid 46 and lower lid 48 are joined to form enclosed assembly 49. Assembly 49 also has one or more seals 49', preferably two or more seals 49', that ensure that
20 enclosed assembly 49 is water tight to prevent injury in the event warmer 10 is exposed to wet conditions.

Warming system 50 has a heat transfer section 51 and a temperature controller 57. Heat transfer section 51 has a coil of tubing 52 and a resistance heater 54. Tubing 52 can be made of aluminum, metal, or plastic that withstands high
5 temperatures. Preferably, tubing 52 is made of aluminum. As shown in Fig. 2, tubing 52 has a flat coil configuration. Preferably, tubing 52 is wound a number of times, preferably about five times.

10 Resistance heater 54 is preferably flat. Heater 54 preferably is made of mica. In this embodiment, heater 54 has a heater cover 55. Cover 55 directs heat from heater 54 towards tubing 52, thus heating the fluid in the tubing. Further, cover
15 55 directs heat away from controller 57 which is described below in more detail. Thus, controller 57 is substantially in thermal isolation from heater 54. Also, the one or more seals 49' cause controller 57 to be in fluid isolation from tubing 52 and supply
40.

20 Resistance heater 54 is connected to, or part of, heat transfer section 51 in a manner that maximizes the surface contact between the resistance heater and the heat transfer section. In a preferred embodiment, heater 54 is connected to

tubing 52 and enclosed by cover 55 to maximize the surface contact between the heater and the tubing and thereby reduce heat loss. Accordingly, warmer 10 maximizes the heat conducted from heater 54 to tubing 52 and ensures a rapid heat up cycle.

5 Further, the volume of tubing 52 is substantially smaller than the volume of container 42. Typically, warmer 10 provides lotion at the desired temperature in about 1 to about 2 minutes.

Warming system 50 also has a temperature controller 57.

10 Controller 57 controls the temperature of lotion warming system 50 so as to provide a rapid heat up cycle, yet avoid overshoot of the desired temperature. Controller 57 is preferably
15 connected to heater 54. For embodiments using an electric pump, controller 57 is connected to pump 22. In a preferred embodiment, controller 57 is an NTC controller having a printed circuit board 56 (hereinafter "PCB") operatively connected to
20 two or more controls 58 (described in detail below). Controller 57 is commonly used in electric curling irons and the like. Alternative control devices can also be utilized such as a thermostat.

Controller 57 has a controller housing 200 sealingly engaged with heater cover 55 through seals 49'. This sealing engagement further ensures that controller 57 and all electrical

components (or other control devices such as a thermostat) contained therein, are substantially thermally isolated from heater 54, and in fluid isolation from supply 40 and tubing 52.

5 Preferably, controller 57 controls the temperature of heater 54 to the desired temperature in a range from about 30° to about 60°C. More preferably, controller 57 controls the temperature of heater 54 to the desired temperature of about 45°C.

10 Controls 58 include preferably an on button, an off button, a red light emitting diode (hereinafter LED), and a green LED. The red LED is used to indicate that warmer 10 is provided with power, e.g., the warmer is plugged in. The red LED and green
15 LED blink to indicate to the user that warmer 10 is warming up the fluid. When the fluid is ready for dispensing at the desired temperature, the red LED turns off and the green LED is on continuously. In the preferred embodiment, controls 58 are located at the top of upper lid 46 and under a membrane keypad
20 (not shown) to ensure that enclosed assembly 49 remains sealed.

Controls 58 also preferably have a temperature control dial (not shown). The temperature control dial is connected to controller 57 to allow the user to vary the desired temperature

of warming system 50 within the ranges provided above. In a preferred embodiment, the temperature control dial is a potentiometer.

5 Alternative positioning of controls 58, as well as methods of control indication, may also be utilized. Controls 58 can also include a red LED, an on/off button and a temperature switch (not shown). The red LED can blink to alert the user that warmer 10 is on, and remains on once the warmer is ready to use. The temperature switch can be a three-position rocker switch that is adapted to set the temperature of heater 54 at one of three positions, such as HI, MEDIUM or LOW.

10
15
Controller 57 controls heater 54 to warm the lotion to the desired temperature while minimizing the overshoot of the desired temperature. Preferably, controller 57 controls heater 54 via an analog circuit, a digital circuit or the like.

20 While the preferred embodiment describes a manual pump device, alternatively an electric device can be utilized. In an alternate embodiment shown in Fig. 6, lotion delivery system 20 has a typical hand operated pump 22' for delivering lotion from lotion supply 20 to lotion warming system 50 and to the user via output section 60. Hand pump 22' has a dispenser plunger 23, a

spring return 24, one or more check valves 25 and a dip tube 26. In this embodiment, tubing 52, preferably aluminum, has a vertical or stacked coil configuration and the resistance heater is a wire heater 54' wound about tubing 52.

5

Controller 57, heater 54' and aluminum tube 52 are sealed from water within enclosed assembly 49. The sealing is achieved preferably by a silicone gasket material 49'. The assembly 49 is stationary as dispense plunger 23 is actuated to dispense lotion from warmer 10. Preferably, assembly 49 is adapted to be connected to container 42 by a connector 47. In a preferred embodiment, connector 47 is a quick connection that simply requires the user to rotate the container not more than 180 degrees with respect to assembly 49.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

15

20

In alternative embodiments, heater 54 and tubing 52 can be replaced with a heat sink 100 and a heating wire 150 in contact with the heat sink. Referring to Figs. 7 through 10, heat sink 100 is shown as cylindrical heat sinks 110, 120 and rectangular heat sinks 130, 140, respectively. However, other alternative shapes may also be utilized for heat sink 100 including cubical or triangular heat sinks. Heat sinks 110, 120, 130, 140 have an axial channel 102 in which the fluid is contained while being heated, and through which the fluid passes when being dispensed.

Heat sinks 110, 130, 140 have channels 105 formed longitudinally therein. Channels 105 house heating wire 150, and maximize heat transfer surface area by partially surrounding the heating wire. Heat sink 120 has channels 107 formed circumferentially therein, preferably in a spiral manner, which also maximizes the heat transfer surface area by partially surrounding heating wire 150. These alternative embodiments that replace heater 54 and tubing 52 reduce the required volume for housing warming system 50 in warmer 10. Further, these alternative embodiments also have the advantage of allowing for heating of the entire warming system including output section 60, shown in Fig. 2. This causes faster heat up times and more efficient use of energy. Heat sink 100 is preferably made of aluminum. More preferably heat sink 100 is made of extruded aluminum.

In the embodiment shown, controller 57 controls heater 54 by using one of three cycles to heat the lotion in tubing 52. Namely, controller 57 includes an initial heat up cycle, an over shoot protection cycle and a maintenance cycle.

Referring to Fig. 11, controller 57 begins the initial heat up cycle when warmer 10 is turned "on", as in step 500. During the initial heat up cycle, controller 57 provides full power to heater 54, as in step 510. The amount of power is about 5 watts

to about 50 watts, preferably about twenty-seven watts.

Controller 57 then determines the fluid temperature in tubing 52, as in step 520. Controller 57 then determines if the fluid temperature in tubing 52 is at or above the anticipation

5 temperature, as in step 530. If the fluid temperature in tubing 52 is at or above the anticipation temperature then the overshoot protection cycle commences, as in step 540. The preset anticipation temperature preferably is between approximately 5°C to approximately 15°C less than the desired
10 temperature.

During the overshoot protection cycle, controller 57 provides reduced power to heater 54, as in step 550.

15 Preferably, the power to the heater is reduced by approximately fifty percent (or preferably to approximately thirteen and one half watts in the preferred embodiment). The power reduction slows the temperature increase as the temperature approaches the desired temperature and, thus, reduces the instance of heater 54 heating the lotion above the desired temperature.

20

Controller 57 then determines the fluid temperature in tubing 52, as in step 560. Controller 57 determines if the fluid temperature in tubing 52 is at or above the desired temperature, as in step 570. If the fluid temperature in tubing

52 is at or above the desired temperature then the maintenance cycle commences, as in step 580.

In step 590, the controller measures the length of time
5 that the heater has been activated. Controller 57 then determines if the activation time is at or above the automatic shut off time period, as in step 600. If the activation time is at or above the automatic shut off time period then controller 57 shuts off all power, as in step 605.

10
15
20
In step 610, if the automatic shut off time period has not been met or exceeded, then controller 57 shuts off power to heater 54. Controller 57 determines the fluid temperature in tubing 52, as in step 620. The controller then determines if the fluid temperature in tubing 52 is at or below the low-level maintenance temperature, as in step 630. Preferably, the preset low-level maintenance temperature is between about 0.5°C to about 10.0°C less than the desired temperature. More preferably, the preset low-level maintenance temperature is
between about 1.0°C to about 1.5°C less than the desired temperature. If the fluid temperature in tubing 52 is at or below the low-level maintenance temperature then controller 57 provides reduced power to heater 54, as in step 640. Preferably, the reduced power to heater 54 is approximately one-

half, e.g., thirteen and one-half watts in the preferred embodiment. Accordingly, during the maintenance cycle, controller 57 maintains the temperature of heater 54 at a point approximately between the low-level maintenance temperature and
5 the desired temperature.

Controller 57 continues to determine the fluid temperature in tubing 52, as in step 650. Controller 57 determines if the fluid temperature in tubing 52 is at or above the desired
10 temperature, as in step 660. If the fluid temperature in tubing 52 is at or above the desired temperature then the controller repeats the steps of the maintenance cycle.

In use, the user activates pump 22 to deliver lotion from
15 container 42 into tubing 52. Tubing 52 is preferably primed with lotion prior to activating heater 54 via control button 58. To active pump 22, the user simply depresses enclosed assembly 49 down with respect to container 42. To deactivate the pump, the user releases enclosed assembly 49, which returns to its up
20 position. Preferably about three cubic centimeters (3 cc) of lotion heated to about the desired temperature is dispensed each time the user depresses enclosed assembly 49.

It should be understood that the foregoing description is only illustrative of the present invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, 5 the present invention is intended to embrace all such alternatives, modifications and variances that fall within the scope of the appended claims.

095905 1333
40001 5403660